

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau(43) International Publication Date  
10 February 2005 (10.02.2005)

PCT

(10) International Publication Number  
**WO 2005/012823 A1**(51) International Patent Classification<sup>7</sup>: **F28F 9/22**(21) International Application Number:  
PCT/JP2004/011309

(22) International Filing Date: 30 July 2004 (30.07.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

2003-284870	1 August 2003 (01.08.2003)	JP
60/497,338	25 August 2003 (25.08.2003)	US
2004-076670	17 March 2004 (17.03.2004)	JP
60/555,706	24 March 2004 (24.03.2004)	US

(71) Applicant (for all designated States except US): **SHOWA DENKO K.K.** [JP/JP]; 13-9, Shiba Daimon 1-chome, Minato-ku, Tokyo 1058518 (JP).

(72) Inventors; and


(75) Inventors/Applicants (for US only): **WATANABE,**

Hirohiko [JP/JP]; c/o SHOWA DENKO K.K., OYAMA REGIONAL OFFICE, 480, Inuzuka 1-chome, Oyama-shi, Tochigi 3238678 (JP). **ARINO, Kouta** [JP/JP]; c/o SHOWA DENKO K.K., OYAMA REGIONAL OFFICE, 480, Inuzuka 1-chome, Oyama-shi, Tochigi 3238678 (JP).

(74) Agents: **HIBI, Norihiko** et al.; c/o KISHIMOTO & CO., 3rd Floor, Inaba Building, 13-18, Nishishinsaibashi 1-chome, Chuo-ku, Osaka-shi, Osaka 5420086 (JP).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

[Continued on next page]

(54) Title: **HEAT EXCHANGER**

(57) Abstract: A heat exchanger 1 comprises a heat exchange core 4 composed of a plurality of heat exchange tubes 9, a refrigerant inlet header 5 and a refrigerant outlet header 6 which are arranged toward one end of each heat exchange tube, and a refrigerant inflow header 7 and a refrigerant outflow header 8 which are arranged toward the other end of each heat exchange tube. The outlet header 6 has interior divided into two spaces 6a, 6b by a flow dividing resistance plate 26, and some of the heat exchange tubes 9 are joined to the outlet header 6 so as to communicate with the space 6b. The resistance plate 26 has a plurality of refrigerant passing holes 27A to 27D formed therein and different in shape and/or size. The outlet header 6 is provided on the outer surface thereof with identification marks 28A to 28D for discriminating the positions of the refrigerant passing holes 27A to 27D and representing the shapes and/or sizes of the holes. The heat exchanger 1 exhibits improved heat exchange performance when used as an evaporator.



(84) **Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

— *with international search report*

— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*